

Smart Positioner YT-3400 / YT-3450

Product Number: YT-3400 / YT-3450 ■ ■ ■ ■ ■ (specify your requirement)

Model	Motion Type	Acting Type	Explosion Proof	Lever Type		Connection Type *	Communication	Option +	Ambient Temp
				Linear	Rotary				
YT-3400	L Linear	S Single	C Ex d IIC T6	1 10~40mm	1 M6 × 34L	1 PT	0 NONE	0 NONE	S -30°C ~ 85°C
YT-3450	R Rotary	D Double		2 20~70mm	2 M6 × 63L	2 NPT	2 + HART	1 +PTM	L -40°C ~ 85°C
				3 50~100mm	3 M8 × 34L			2 +L/S	
				4 100~150mm	4 M8 × 63L			3 +PTM+L/S	
					5 NAMUR				

* YT-3450 is available for NPT1/4 connection type ONLY.


+ L/S: DC24V and Transistor Type Switch.



YT-3400R



YT-3450R



Item · Type	YT-3400	YT-3450
Input Signal	4~20mA DC	
Supply Pressure	0.14~0.7MPa(1.4~7 bar)	
Stroke	Linear Type	10~150mm
	Rotary type	0 ~ 90°
Impedance	Max.450Ω @ 20mA DC	
Air Connection	PT(NPT)1/4	NPT 1/4
Gauge Connection	PT(NPT)1/8	NPT 1/8
Conduit	PF 1/2 (G 1/2)	
Ambient Temp.	Standard Type.	-30°C ~ 85°C (-22~185° F)
	Low Temp Type.	-40°C ~ 85°C (-40~185° F)
	Explosion Temp.	-40°C~70°C(T6) / -40°C~85°C(T5)
	LCD Operating Temp.	-30°C ~ 85°C (-22~185° F)
Linearity	±0.5% F.S.	
Hysteresis	±0.5% F.S.	
Sensitivity	±0.2% F.S.	
Repeatability	±0.3% F.S.	
Air Consumption	Below 2LPM (sup=0.14MPa)	
Flow Capacity	70LPM (sup=0.14MPa)	
Output Characteristics	Linear, EQ%, Quick Open user set (16 Point)	
Material	Aluminum Diecasting	Stainless Steel 316
Enclosure	IP66	
Explosion Proof type	Ex d IIC T6 / T5	
Weight	3.4kg (7.5lb)	7.0kg(15.4lb)

YT-3400 Smart Valve Positioner accurately controls valve stroke, according to input signal of 4-20mA being delivered from controller.

- Auto calibration
- PID control
- HART communication
- Auto/Manual switch
- Feedback signal
- 4 buttons for local control
- LCD display
- Limit switches